

## THERMOPITTURA

### Indoor paint

Rev. 3 - 04\_06\_25



### General Description

This is a reflective thermal interior paint, highly breathable, used as the finishing coat for the **AFONTERMO IL NANOCAPPOTTO** system. The formulation contains light-fast pigments, thermal inert fillers, drying resins and water. The product appears to be creamy, yogurt-like white appearance and thixotropic viscosity. The product provides excellent water-vapour permeability, good thermal insulation properties and outstanding frost resistance.

**Tinting:** can be tinted only with mineral oxide pigments in light shades.

### Warranty

In addition to the statutory warranty, the product is covered by a Product Liability (RC Prodotti) insurance policy underwritten by a leading Italian insurance company.

### Packaging and Coverage

14-L. bucket. Yield: = 45 m<sup>2</sup> per bucket for one coat of paint.

### Substrate Preparation

For refurbishments, remove any existing coatings on the masonry—especially those in poor condition and even more so if they are washable or synthetic paints. If washable paints are present, strip them off completely and apply a first coat of **FISSATIVO AFON CASA** (breathable, non-film-forming, water-based primer) to the substrate.

Before application, walls must be clean and dry, with no traces of mould - any mould present must be completely removed or treated.

### Application

**Dilution:** Thin with clean water up to a maximum of 10 %. Mix thoroughly with an electric mixer. Thanks to its thixotropic nature, the product can be laid in one coat, using a roller or a brush. If the paint needs colouring we recommend applying two coats for an optimal result.

### Storage

Store indoors, in closed containers, protected from direct sunlight.